

RELATIONS OF CONTEXTUAL GRAMMARS WITH STRICTLY LOCALLY TESTABLE SELECTION LANGUAGES

JÜRGEN DASSOW¹ AND BIANCA TRUTHE^{2,*}

Abstract. We continue the research on the generative capacity of contextual grammars where contexts are adjoined around whole words (externally) or around subwords (internally) which belong to special regular selection languages. All languages generated by contextual grammars where all selection languages are elements of a certain subregular language family form again a language family. We investigate the computational capacity of contextual grammars with strictly locally testable selection languages and compare those families to families which are based on finite, monoidal, nilpotent, combinational, definite, suffix-closed, ordered, commutative, circular, non-counting, power-separating, or union-free languages. With these results, also an open problem regarding ordered and non-counting selection languages is solved.

Mathematics Subject Classification. 68Q42, 68Q45.

Received February 7, 2023. Accepted October 17, 2023.

1. INTRODUCTION

Contextual grammars were introduced by Solomon Marcus in [17] as a formal model that might be used for the generation of natural languages. The derivation steps consist of adjoining contexts to given sentences starting from a finite set. A context is given by a pair (u, v) of words. The external adjoining to a word x gives the word uxv and the internal adjoining gives all words $x_1ux_2vx_3$ with $x_1x_2x_3 = x$. Contextual grammars where the contexts are adjoined ex- or internally are called external or internal contextual grammars, respectively. The internal case is different from the case of external contextual grammars, as there are two main differences between the ways in which words are derived. In the case of internal contextual grammars, it is possible that the insertion of a context into a sentential form can be done at more than one place, such that the derivation becomes in some sense non-deterministic; in the case of external grammars, once a context was selected, there is at most one way to insert it: wrapped around the sentential form, when this word is in the selection language of the context. If a context can be added internally, then it can be added arbitrarily often (because the

Keywords and phrases: Contextual grammars, external and internal derivation modes, selection languages, subregular families of languages.

¹ Fakultät für Informatik, Otto-von-Guericke-Universität Magdeburg, Postfach 4120, 39106 Magdeburg, Germany.

² Institut für Informatik, Justus-Liebig-Universität Giessen, Arndtstr. 2, 35392 Giessen, Germany.

* Corresponding author: bianca.truthe@informatik.uni-giessen.de

subword where the context is wrapped around does not change) which does not necessarily hold for external grammars.

By the linguistic motivation, it is natural to require that certain contexts can only be used if the subword x or x_2 (where the contexts are to be adjoined) satisfies some condition. One possibility is to require that the words x or x_2 have to belong to a language S , called the selection language, associated with the context. Mostly, it is also required that the language S belongs to some language family F . The first investigations in this direction were presented in [15] where the language families of the Chomsky hierarchy were chosen as F ; for further information, we refer to [15, 19, 22] and references therein.

By practical reasons, however, it is natural to consider ‘simple’ languages as selection languages or to restrict F to be a language family of ‘simple’ languages. Very often subregular language families were used as an approach to simplification. Typical examples for such languages are finite, monoidal, nilpotent, combinational, definite, suffix-closed, commutative, circular, ordered, non-counting, power-separating, strictly locally (k -)testable, and union-free languages and languages which are defined by syntactic restrictions (as the families of languages which can be accepted by deterministic finite automata with at most n states or can be generated by right-linear grammars with at most n nonterminals/productions/symbols).

The study of contextual grammars with selection in special regular sets was started in [3] and continued in [4, 7, 8, 28]. For the families defined by syntactic restrictions, in the external case as well as in the internal case, infinite hierarchies with respect to all parameters mentioned above were obtained. Moreover, the hierarchy of external contextual languages with selection by the subregular families mentioned above was almost completely determined. But for the internal derivation mode, the results concern only finite, monoidal, nilpotent, combinational, definite, suffix-closed, commutative, circular, and ordered selection languages.

A recent survey can be found in [28].

In the present paper, we first add some relations between the families of strictly locally (k -)languages to some other families mentioned above.

For external contextual grammars with selections, we solve open problems regarding the relation between the families obtained by ordered, non-counting, and strictly locally 1-testable selection languages.

For internal contextual grammars, we investigate the impact of strictly locally testable selection languages on the generative capacity and compare it to those of the families which are based on finite, monoidal, nilpotent, combinational, definite, suffix-closed, ordered, commutative, circular, non-counting, power-separating, or union-free selection languages.

In the end, we mention some open problems.

This paper is an extension of [9].

2. PRELIMINARIES

After giving some notations used in this paper, we first recall the subregular families of languages under investigation and then recall the contextual grammars with external or internal language generating modes.

We assume that the reader is familiar with the basic concepts of the theory of automata and formal languages. For details, we refer to [22].

Given an alphabet V , we denote by V^* and V^+ the set of all words and the set of all non-empty words over V , respectively. The empty word is denoted by λ . By V^k and $V^{\leq k}$ for some natural number k , we denote the set of all words of the alphabet V with exactly k letters and the set of all words over V with at most k letters, respectively. For a word w , we denote the length of w by $|w|$.

A deterministic finite automaton is a quintuple $\mathcal{A} = (V, Z, z_0, F, \delta)$ where V is a non-empty, finite set, called the input alphabet, Z is a non-empty, finite set whose elements are called states, $z_0 \in Z$ which is the so-called start state, $F \subseteq Z$ whose elements are called accepting states, and δ is a transition mapping $\delta : Z \times V \rightarrow Z$. The transition mapping δ is extended to a function $\delta^* : Z \times V^* \rightarrow Z$ as follows: $\delta^*(z, \lambda) = z$ for all $z \in Z$ and $\delta^*(z, aw) = \delta^*(\delta(z, a), w)$ for $z \in Z$, $a \in V$, and $w \in V^*$. We denote the extended function also by δ .

2.1. Subregular language families

2.1.1. Definitions of Subregular Language Families

We consider the following restrictions for regular languages. Let L be a language over an alphabet V . We say that the language L – with respect to the alphabet V – is

- *monoidal* if and only if $L = V^*$,
- *nilpotent* if and only if it is finite or its complement $V^* \setminus L$ is finite,
- *combinational* if and only if it has the form $L = V^*X$ for some subset $X \subseteq V$,
- *definite* if and only if it can be represented in the form $L = A \cup V^*B$ where A and B are finite subsets of V^* ,
- *suffix-closed* (or *fully initial* or *multiple-entry* language) if and only if, for any two words $x \in V^*$ and $y \in V^*$, the relation $xy \in L$ implies the relation $y \in L$,
- *ordered* if and only if the language is accepted by some deterministic finite automaton

$$\mathcal{A} = (V, Z, z_0, F, \delta)$$

with an input alphabet V , a finite set Z of states, a start state $z_0 \in Z$, a set $F \subseteq Z$ of accepting states and a transition mapping δ where $(Z, \preceq)$ is a totally ordered set and, for any input symbol $a \in V$, the relation $z \preceq z'$ implies $\delta(z, a) \preceq \delta(z', a)$,

- *commutative* if and only if it contains with each word also all permutations of this word,
- *circular* if and only if it contains with each word also all circular shifts of this word,
- *non-counting* (or *star-free*) if and only if there is a natural number $k \geq 1$ such that, for any three words $x \in V^*$, $y \in V^*$, and $z \in V^*$, it holds $xy^kz \in L$ if and only if $xy^{k+1}z \in L$,
- *power-separating* if and only if, there is a natural number $m \geq 1$ such that for any word $x \in V^*$, either the equality $J_x^m \cap L = \emptyset$ or the inclusion $J_x^m \subseteq L$ holds where $J_x^m = \{x^n \mid n \geq m\}$,
- *union-free* if and only if L can be described by a regular expression which is only built by product and star,
- *strictly locally k -testable* if and only if there are three subsets B , I , and E of V^k such that any word $a_1a_2 \dots a_n$ with $n \geq k$ and $a_i \in V$ for $1 \leq i \leq n$ belongs to the language L if and only if $a_1a_2 \dots a_k \in B$, $a_{j+1}a_{j+2} \dots a_{j+k} \in I$ for $1 \leq j \leq n - k - 1$, and $a_{n-k+1}a_{n-k+2} \dots a_n \in E$,
- *strictly locally testable* if and only if it is strictly locally k -testable for some natural number k .

We remark that monoidal, nilpotent, combinational, definite, ordered, union-free, and strictly locally (k) -testable languages are regular, whereas non-regular languages of the other types mentioned above exist. Here, we consider among the commutative, circular, suffix-closed, non-counting, and power-separating languages only those which are also regular.

These languages are of interest because they have often very different characterizations. We mention here four examples.

- A language is non-counting if and only if it can be obtained from the empty set and the languages consisting of the empty word or of letters of the alphabet by using union, concatenation, and complement (see [18]).
- A language is non-counting if and only if its syntactic monoid is aperiodic (Schützenberger’s Theorem).
- A language is nilpotent if and only if its syntactic monoid is nilpotent.
- A language is suffix-closed if and only if it can be accepted by a finite automaton where all states serve as initial states (see [12]).

Moreover, the languages are sometimes of interest by ‘practical’ reasons. Again, we mention four facts.

- To check membership of a definite language, it is sufficient to consider only suffixes of a certain length.
- To check membership of a strictly locally k -testable language, it is sufficient to move a window of size k over the word.

- Strictly locally testable are learnable in the limit by positive data (see [10])
- Each regular language can be obtained from a strictly locally 2-testable language by a homomorphism (Medvedev's Theorem).

Some properties of the languages of the classes mentioned above can be found in [23] (monoids), [11] (nilpotent languages), [13] (combinational and commutative languages), [20] (definite languages), [12] and [2] (suffix-closed languages), [24] (ordered languages), [16] (circular languages), [18] (non-counting and strictly locally testable languages), [25] (power-separating languages), [1] (union-free languages).

By FIN , MON , NIL , $COMB$, DEF , SUF , ORD , $COMM$, $CIRC$, NC , PS , UF , SLT_k (for any natural number $k \geq 1$), SLT , and REG , we denote the families of all finite, monoidal, nilpotent, combinational, definite, regular suffix-closed, ordered, regular commutative, regular circular, regular non-counting, regular power-separating, union-free, strictly locally k -testable, strictly locally testable, and regular, languages, respectively.

A strictly locally testable language characterized by three finite sets B , I , and E as above which includes additionally a finite set F of words which are shorter than those of the sets B , I , and E is denoted by $[B, I, E, F]$.

As the set of all families under consideration, we set

$$\mathcal{F} = \{FIN, MON, NIL, COMB, DEF, SUF, ORD, COMM, CIRC, NC, PS, UF\} \\ \cup \{SLT\} \cup \{SLT_k \mid k \geq 1\}.$$

2.1.2. Hierarchy of Subregular Language Families

Many inclusion relations and incomparabilities between these families have been proved in the past, see [28] for a survey. We now insert the families of the strictly locally (k -)testable languages into the existing hierarchy.

The families of strictly locally k -testable languages form an infinite hierarchy of proper inclusions. This is shown in [21] with the witness languages

$$L_h = \{ab^h\}^+ \in SLT_{h+1} \setminus SLT_h \text{ for } h \geq 1.$$

From [18], we know the proper inclusion $SLT \subset NC$. In [4], the proper inclusions $COMB \subset SLT_1$ and $DEF \subset SLT$ as well as the incomparability of each family SLT_k for $k \geq 1$ with the families FIN , NIL , and DEF were mentioned but not proved. This will be done in the sequel. We first give a witness language which will be useful in all these proofs.

Lemma 2.1. *Let $L_{SLT_1, \neg DEF} = \{a\} \cup \{ab^n a \mid n \geq 0\}$. Then*

$$L_{SLT_1, \neg DEF} \in SLT_1 \setminus DEF.$$

Proof. The language $L_{SLT_1, \neg DEF}$ can be represented as $[\{a\}, \{b\}, \{a\}, \emptyset]$, hence $L_{SLT_1, \neg DEF} \in SLT_1$.

Suppose, this language is definite. Then there are two finite subsets $D_s \subset \{a, b\}^*$ and $D_e \subset \{a, b\}^*$ such that

$$L_{SLT_1, \neg DEF} = D_s \cup \{a, b\}^* D_e.$$

Let $k = \max\{|w| \mid w \in D_s \cup D_e\} + 1$. The word $ab^k a$ belongs to the language $L_{SLT_1, \neg DEF}$ but not to the subset D_s due to its length. Hence, $ab^k a \in \{a, b\}^* D_e$ and also

$$ab^k a \in \{a, b\}^+ D_e$$

due to the length of the word. Then we have also $b^{k+1} a \in \{a, b\}^+ D_e$ and, therefore,

$$b^{k+1} a \in L_{SLT_1, \neg DEF}$$

which is a contradiction. Thus, $L_{SLT_1, \neg DEF} \notin DEF$. $\square$

The language $L_{SLT_1, \neg DEF}$ is a witness language for the properness of the three inclusions stated in the following lemmas.

Lemma 2.2. *The proper inclusion $MON \subset SLT_1$ holds.*

Proof. We first prove that MON is included in SLT_1 . Let L be a monoidal language over an alphabet V . Then $L = V^*$. With $[V, V, V, \lambda]$, we have a representation of the language L as a strictly locally 1-testable language. Hence, $MON \subseteq SLT_1$.

A witness language for the properness is the language $L_{SLT_1, \neg DEF}$ which, according to Lemma 2.1, belongs to the class SLT_1 but not to DEF and not to MON because $MON \subseteq DEF$. $\square$

Lemma 2.3. *The proper inclusion $COMB \subset SLT_1$ holds.*

Proof. We first prove that $COMB$ is included in SLT_1 . Let L be a combinational language over an alphabet V . Then $L = V^*X$ for some subset $X \subseteq V$. With $[V, V, X, \emptyset]$, we have a representation of the language L as a strictly locally 1-testable language. Hence, $COMB \subseteq SLT_1$.

A witness language for the properness is the language $L_{SLT_1, \neg DEF}$ which, according to Lemma 2.1, belongs to the class SLT_1 but not to DEF and not to $COMB$ because $COMB \subseteq DEF$. $\square$

Lemma 2.4. *The proper inclusion $DEF \subset SLT$ holds.*

Proof. We first prove $DEF \subseteq SLT$. Let L be a definite language over an alphabet V . Then $L = D_s \cup V^*D_e$ for some finite subsets $D_s \subset V^*$ and $D_e \subset V^*$. Let $k = \max\{|w| \mid w \in D_s \cup D_e\} + 1$. Further, let

- $F = \{w \mid w \in L \cap V^{\leq k-1}\}$ be the set of all words of L with a length smaller than k ,
- $B = V^k$ and $I = V^k$ the set of all words over the alphabet V with a length of k ,
- $E = V^*D_e \cap V^k$ the set of all words of the set V^*D_e with length k ,

and L' be the strictly locally k -testable language represented by $[B, I, E, F]$. We now prove that $L = L'$ holds.

We first show $L \subseteq L'$. Let $w \in L$. If $|w| < k$, then $w \in F$ and, hence, $w \in L'$. Otherwise, $w \in V^*D_e$ and there are words w_0 and w_1 such that $w = w_1w_0$ and $w_0 \in V^*D_e \cap V^k$ (the word w_0 is the suffix of w of length k). Every subword of w of length k belongs to the set V^k . Hence, the prefix of w of length k belongs to the set B , every proper infix of w of length k belongs to the set I , and the suffix w_0 belongs to the set E . Therefore, we have $w \in L'$ also in this case.

We now show $L' \subseteq L$. Let $w \in L'$. If $w \in F$, then $w \in L \cap V^{\leq k-1}$ and, hence, $w \in L$. Otherwise, the length $m = |w|$ of w is at least k and the word w is composed of m letters $x_i \in V$ for $1 \leq i \leq m$ such that $w = x_1x_2 \dots x_m$. Then we have for the prefix $x_1x_2 \dots x_k \in B$, for each infix $x_{j+1}x_{j+2} \dots x_{j+k} \in I$ for $1 \leq j \leq m-1-k$, and for the suffix $x_{m-k+1}x_{m-k+2} \dots x_m \in E$. Therefore, $x_{m-k+1}x_{m-k+2} \dots x_m \in V^*D_e$ and $x_1x_2 \dots x_{m-k} \in V^*$. Hence, $w \in V^*D_e$ and $w \in L$.

Since $L = L'$ and $L' \in SLT_k$ by construction, we also have that $L \in SLT_k$ and, thus, also $L \in SLT$.

A witness language for the properness of the inclusion $DEF \subseteq SLT$ is the language $L_{SLT_1, \neg DEF}$ which, according to Lemma 2.1, belongs to the class SLT_1 and therefore also to SLT but not to DEF . $\square$

The language $L_{SLT_1, \neg DEF}$ from Lemma 2.1 serves also partially for proving the incomparability of the families of the strictly locally k -testable languages with the families of the finite languages, of the nilpotent languages, and of the definite languages.

Lemma 2.5. *The classes SLT_k for $k \geq 1$ are incomparable to the classes FIN , NIL , and DEF .*

Proof. Due to the inclusion relations, it suffices to show that there is a language in the class SLT_1 (which belongs also to each other family SLT_k for $k > 1$) but which is not definite (and hence neither nilpotent nor finite) and that there are languages L_k (for $k \geq 1$) which are finite (and, hence, nilpotent and definite) but not strictly locally k -testable.

A language for the first case is $L_{SLT_1, \neg DEF}$ from Lemma 2.1 since

$$L_{SLT_1, \neg DEF} \in SLT_1 \setminus DEF.$$

Languages for the other incomparabilities are $L_k = \{a\}^{k+1}$ for $k \geq 1$. Every such language L_k is finite. Let k be a natural number. Suppose that the language L_k is also strictly locally k -testable. Then it is represented by $[\{a\}^k, \emptyset, \{a\}^k, \emptyset]$. But then, we also have $a^k \in L_k$ which is a contradiction. Hence, $L_k \in FIN \setminus SLT_k$ for $k \geq 1$. $\square$

The incomparabilities of the families of the strictly locally (k -)testable languages to the families UF of the union-free languages, SUF of the suffix-closed languages, $COMM$ of the commutative languages, and $CIRC$ of the circular languages follow, due to the inclusion relations, from the incomparabilities of the classes UF , SUF , $COMM$, and $CIRC$ to the classes $COMB$ of the combinational languages and NC of the non-counting languages which were proved in [14].

Regarding the class ORD of the ordered languages, we have the relations below for which we use the witness languages given in the following lemmas.

Lemma 2.6. *Let $L_{ORD, \neg SLT} = \{a\}^* \{b\} \{a\}^*$. Then $L_{ORD, \neg SLT} \in ORD \setminus SLT$.*

Proof. The language $L_{ORD, \neg SLT}$ is accepted by a deterministic finite automaton where the transition function is given by the following table (the order is $z_0 \preceq z_1 \preceq z_2$, start state is z_0 , accepting state is z_1):

δ	z_0	z_1	z_2
a	z_0	z_1	z_2
b	z_1	z_2	z_2

Hence, $L_{ORD, \neg SLT} \in ORD$.

Assume that $L_{ORD, \neg SLT} = [B, I, E, F] \in SLT_k$ for some natural number $k \geq 1$. Since $a^k b a^{2k} \in L_{ORD, \neg SLT}$, we obtain $a^k \in B$, $a^{k-r} b a^{r-1} \in I$ for $1 \leq r \leq k$, $a^k \in I$, and $a^k \in E$. Consequently, we have $a^k b a^k b a^{2k} \in L_{ORD, \neg SLT}$ which contradicts the structure of words in $L_{ORD, \neg SLT}$. Hence, $L_{ORD, \neg SLT} \notin SLT$. $\square$

Lemma 2.7. *Let $L_{SLT_2, \neg ORD} = \{a\}^* \cup \{b\}^* \cup \{c\}^*$. Then*

$$L_{SLT_2, \neg ORD} \in SLT_2 \setminus ORD.$$

Proof. It is easy to see that

$$L_{SLT_2, \neg ORD} = [\{aa, bb, cc\}, \{aa, bb, cc\}, \{aa, bb, cc\}, \{\lambda, a, b, c\}].$$

Hence, $L_{SLT_2, \neg ORD} \in SLT_2$.

Assume that the language $L_{SLT_2, \neg ORD}$ is accepted by an ordered deterministic finite automaton $\mathcal{A} = (\{a, b, c\}, Z, z_0, F, \delta)$. For any word $w \in \{a, b, c\}^*$, let $[w]$ be the state of $\mathcal{A}$ after reading w : $[w] = \delta(z_0, w)$ (we identify the equivalence classes of the Myhill–Nerode relation with the states). The states $[a]$, $[b]$, and $[c]$ are pairwise different since $[aa] \in F$ but $[ba] \notin F$ and $[ca] \notin F$ and $[bb] \in F$ but $[cb] \notin F$. Let $[a] \prec [b] \prec [c]$ (due to the structure of $L_{SLT_2, \neg ORD}$, we do not need to consider the other possibilities). The state $[\lambda]$ is also different from each of the states $[a]$, $[b]$, and $[c]$ ($[\lambda b] \in F$ but $[ab] \notin F$, $[\lambda a] \in F$ but $[ba] \notin F$ and $[ca] \notin F$). We now conclude a contradiction for any position of $[\lambda]$ in the assumed order.

- (1) $[\lambda] \prec [a]$: Then $[b] \preceq [ab]$. Since $[a] \prec [b]$, we also have $[ab] \preceq [bb]$. Hence, $[b] \preceq [ab] \preceq [bb]$. By iteration, we obtain

$$[b] \preceq [ab] \preceq [bb] \preceq \cdots \preceq [ab^i] \preceq [bb^i].$$

Since there are only finitely many states, there is a number $n \geq 1$ such that $[b^n] = [ab^n] = [bb^n]$ but $[ab^n] \notin F$ whereas $[bb^n] \in F$ which is a contradiction.

- (2) $[a] \prec [\lambda] \prec [b]$: Then $[c] \preceq [bc]$. Since $[b] \prec [c]$, we also have $[bc] \preceq [cc]$. Hence, $[c] \preceq [bc] \preceq [cc]$. By iteration, we obtain

$$[c] \preceq [bc] \preceq [cc] \preceq \cdots \preceq [bc^i] \preceq [cc^i].$$

Since there are only finitely many states, there is a number $n \geq 1$ such that $[c^n] = [bc^n] = [cc^n]$ but $[bc^n] \notin F$ whereas $[cc^n] \in F$ which is a contradiction.

- (3) $[b] \prec [\lambda] \prec [c]$: Then $[ba] \preceq [a]$. Since $[a] \prec [b]$, we also have $[aa] \preceq [ba]$. Hence, $[aa] \preceq [ba] \preceq [a]$. By iteration, we obtain

$$[aa^i] \preceq [ba^i] \preceq \cdots [aa] \preceq [ba] \preceq [a].$$

Since there are only finitely many states, there is a number $n \geq 1$ such that $[aa^n] = [ba^n] = [a^n]$ but $[ba^n] \notin F$ whereas $[a^n] \in F$ which is a contradiction.

- (4) $[c] \prec [\lambda]$: Then $[cb] \preceq [b]$. Since $[b] \prec [c]$, we also have $[bb] \preceq [cb]$. Hence, $[bb] \preceq [cb] \preceq [b]$. By iteration, we obtain

$$[bb^i] \preceq [cb^i] \preceq \cdots [bb] \preceq [cb] \preceq [b].$$

Since there are only finitely many states, there is a number $n \geq 1$ such that $[bb^n] = [cb^n] = [b^n]$ but $[cb^n] \notin F$ whereas $[b^n] \in F$ which is a contradiction.

Hence, the language $L_{SLT_2, \neg ORD}$ is not accepted by an ordered deterministic finite automaton: $L_{SLT_2, \neg ORD} \notin ORD$. $\square$

With the help of the languages from the Lemmas 2.6 and 2.7, we prove the following results.

Lemma 2.8. *The proper inclusion $SLT_1 \subset ORD$ holds.*

Proof. We first prove the inclusion $SLT_1 \subseteq ORD$ and show how a strictly locally 1-testable language L over an alphabet V can be accepted by an ordered automaton. For such a language $L = [B, I, E, F]$, we have $B \subseteq V$, $I \subseteq V$, $E \subseteq V$, and $F \subseteq \{\lambda\}$. We construct the following deterministic finite automaton:

$$\mathcal{A} = (V, \{z_0, z_1, \dots, z_5\}, z_1, Z_f, \delta)$$

where

$$Z_f = \{z_2, z_4\} \cup \begin{cases} \{z_1\}, & \text{if } \lambda \in F, \\ \emptyset, & \text{otherwise,} \end{cases}$$

and the transition function δ is given by the diagram in Figure 1 (z_1 is an accepting state if and only if $\lambda \in F$).

In order to prove that $L(\mathcal{A}) = L$, we first show that every word $w \in L$ is accepted by $\mathcal{A}$ and then that every word $w \in V^* \setminus L$ is not accepted by $\mathcal{A}$.




FIGURE 1. Ordered Automaton for accepting a strictly locally 1-testable language $[B, I, E, F]$.

Let $w \in L$.

If $|w| = 0$, then $w = \lambda$, $\lambda \in L$, and, hence, $\lambda \in F$. Thus, $\delta(z_1, w) = z_1 \in Z_f$. Hence, $w \in L(\mathcal{A})$.

If $|w| = 1$, then $w \in B \cap E$ and $\delta(z_1, w) = z_2 \in Z_f$. Hence, $w \in L(\mathcal{A})$.

If $|w| = 2$, then $w \in BE$ and $\delta(z_1, w) \in \{z_2, z_4\} \subset Z_f$. Hence, $w \in L(\mathcal{A})$.

If $|w| \geq 3$, then $w \in BI^+E$. Let w_i for $1 \leq i \leq |w|$ be the letters of w such that $w = w_1 w_2 \dots w_{|w|}$. Then $\delta(z_1, w_1) \in \{z_2, z_3\}$. For $2 \leq i \leq |w| - 1$, we have $\delta(z_1, w_1 \dots w_i) \in \{z_2, z_3\}$. Hence, $\delta(z_1, w) \in \{z_2, z_4\} \subset Z_f$. Thus, also in this case, $w \in L(\mathcal{A})$.

Let now $w \in V^* \setminus L$.

If $|w| = 0$, then $w = \lambda$, but $\lambda \notin L$, and, hence, $\lambda \notin F$. Thus, $\delta(z_1, w) = z_1 \notin Z_f$. Hence, $w \notin L(\mathcal{A})$.

If $|w| = 1$, then $w \in V$ but $w \notin B$ or $w \notin E$. If $w \notin B$, then $\delta(z_1, w) = z_0 \notin Z_f$. If $w \in B$ but $w \notin E$, then $\delta(z_1, w) = z_3 \notin Z_f$. Hence, in both these cases, $w \notin L(\mathcal{A})$.

If $|w| \geq 2$, let w_i for $1 \leq i \leq |w|$ be the letters of w such that $w = w_1 w_2 \dots w_{|w|}$. Then $w_1 \notin B$ or $w_{|w|} \notin E$ or there is an index i with $2 \leq i \leq |w| - 1$ such that $w_i \notin I$. If $w_1 \notin B$, then $\delta(z_1, w) = z_0 \notin Z_f$ and $w \notin L(\mathcal{A})$. If $w_1 \in B$, then $\delta(z_1, w_1) \in \{z_2, z_3\}$. If $|w| = 2$, then $w_2 \notin E$ and $\delta(z_2, w_2) \in \{z_3, z_5\}$ and $\delta(z_3, w_2) \in \{z_3, z_5\}$. Thus, $w \notin L(\mathcal{A})$.

Let $|w| \geq 3$. If $w_2 \notin I$, then $\delta(z_2, w_2) \in \{z_4, z_5\}$ and $\delta(z_3, w_2) \in \{z_4, z_5\}$. Hence, $\delta(z_1, w) = z_5 \notin Z_f$ and $w \notin L(\mathcal{A})$. For $i = 2, \dots, |w| - 1$, as long as $w_i \in I$, we have $\delta(z_2, w_2 \dots w_i) \in \{z_2, z_3\}$ and $\delta(z_3, w_2 \dots w_i) \in \{z_2, z_3\}$. If $w_i \notin I$ for some index i with $3 \leq i \leq |w| - 1$ (and $w_j \in I$ for $2 \leq j < i$), then $\delta(z_2, w_i) \in \{z_4, z_5\}$ and $\delta(z_3, w_i) \in \{z_4, z_5\}$. Hence, $\delta(z_1, w) = z_5 \notin Z_f$ and $w \notin L(\mathcal{A})$. If $w_i \in I$ for all i with $2 \leq i \leq |w| - 1$, then $w_{|w|} \notin E$ and $\delta(z_1, w_1 \dots w_{|w|-1}) \in \{z_2, z_3\}$. Hence, $\delta(z_1, w) \in \{z_3, z_5\}$. Thus, $w \notin L(\mathcal{A})$.

This concludes the proof that $L = L(\mathcal{A})$. We now prove that the automaton $\mathcal{A}$ is ordered, especially that the semi-order $z_0 \preceq z_1 \preceq \dots \preceq z_5$ is preserved under the transition function δ .

The transition of an input symbol x depends on its membership to the sets B , I , and E only. Hence, we represent a symbol x by a triple (b_x, i_x, e_x) with

$$b_x = \begin{cases} 1, & \text{if } x \in B, \\ 0, & \text{otherwise,} \end{cases} \quad i_x = \begin{cases} 1, & \text{if } x \in I, \\ 0, & \text{otherwise,} \end{cases} \quad e_x = \begin{cases} 1, & \text{if } x \in E, \\ 0, & \text{otherwise.} \end{cases}$$

On the other hand, we define, for each triple $t \in \{0, 1\}^3$, a set V_t as the set of all symbols of V which are represented by t : $V_t = \{x \mid (b_x, i_x, e_x) = t\}$. We extend the transition function δ to a mapping $\hat{\delta} : Z \times \mathcal{P}(V) \rightarrow \mathcal{P}(Z)$ by $\hat{\delta}(z, M) = \{\delta(z, x) \mid x \in M\}$ ($\mathcal{P}(V)$ and $\mathcal{P}(Z)$ are the power sets of V and Z , respectively). For any two symbols x and y which are represented by the same triple, $(b_x, i_x, e_x) = (b_y, i_y, e_y)$, we have $\delta(z, x) = \delta(z, y)$ for all $z \in Z$ and, therefore, $\hat{\delta}(z, \{x, y\}) = \{\delta(z, \{x\})\} = \{\delta(z, \{y\})\}$. So, for each triple $t \in \{0, 1\}^3$, the set $\hat{\delta}(z, V_t)$ is a singleton set for each state $z \in Z$. The transition table is as follows (instead of V_t or its elements, we write

t in the first column, and the unique element of $\hat{\delta}(z, V_t)$ in each entry):

$\hat{\delta}$	z_0	z_1	z_2	z_3	z_4	z_5
$(0, 0, 0)$	z_0	z_0	z_5	z_5	z_5	z_5
$(0, 0, 1)$	z_0	z_0	z_4	z_4	z_5	z_5
$(0, 1, 0)$	z_0	z_0	z_3	z_3	z_5	z_5
$(0, 1, 1)$	z_0	z_0	z_2	z_2	z_5	z_5
$(1, 0, 0)$	z_0	z_3	z_5	z_5	z_5	z_5
$(1, 0, 1)$	z_0	z_2	z_4	z_4	z_5	z_5
$(1, 1, 0)$	z_0	z_3	z_3	z_3	z_5	z_5
$(1, 1, 1)$	z_0	z_2	z_2	z_2	z_5	z_5

With the order $z_0 \prec z_1 \prec \dots \prec z_5$, we see in the table that the states in every row are in ascending order:

$$z'_0 \preceq z'_1 \preceq z'_2 \preceq z'_3 \preceq z'_4 \preceq z'_5$$

with $z'_i \in \hat{\delta}(z_i, V_t)$ holds for every triple $t \in \{0, 1\}^3$. Since $\hat{\delta}(z_i, V_t) = \{z'_i\}$ is equivalent to $\delta(z_i, x) = z'_i$ for all $x \in V_t$, $t \in \{0, 1\}^3$, and $0 \leq i \leq 5$, the semi-order is also preserved by the function δ . Hence, the automaton $\mathcal{A}$ is ordered. By this construction, we have proved the inclusion $SLT_1 \subseteq ORD$.

The properness of the inclusion follows from Lemma 2.6 with the witness language $L_{ORD, \neg SLT}$. $\square$

Lemma 2.9. *The classes SLT and SLT_k for $k \geq 2$ are incomparable to the class ORD .*

Proof. From Lemma 2.6, we know that there is a language (namely $L_{ORD, \neg SLT}$) in ORD which does not belong to any class SLT_k for $k \geq 2$ and, hence, also not to the class SLT .

From Lemma 2.7, we know that there is a language (namely $L_{SLT_2, \neg ORD}$) in SLT_2 and, hence, also in SLT_k for $k > 2$ and SLT which does not belong to the class ORD . $\square$

If we combine these results with those mentioned in [28], we obtain the following statement.

Theorem 2.10. *The inclusion relations presented in Figure 2 hold. An arrow from an entry X to an entry Y depicts the proper inclusion $X \subset Y$; if two families are not connected by a directed path, then they are incomparable.*

An edge label in Figure 2 refers to a paper or a lemma in the present paper where the respective inclusion is proved. The other inclusions are easy to see. Proofs for the incomparabilities which are not related to strictly locally testable languages can be found in [27].

2.2. Contextual grammars

Let $F \in \mathcal{F}$ be a family of languages. A contextual grammar with selection in F is a triple $G = (V, \mathcal{P}, A)$ where

- V denotes an alphabet,
- $\mathcal{P}$ is a finite set of pairs (S, C) with a language S over some subset U of the alphabet V which belongs to the family F with respect to the alphabet U and a finite set $C \subset V^* \times V^*$,
- A denotes a finite subset of V^* .

The set V is called the basic alphabet; for a selection pair $(S, C) \in \mathcal{P}$, the language S is called a selection language and the set C is called a set of contexts of the grammar G ; the elements of A are called axioms.

We now define the derivation modes for contextual grammars with selection.

3. RESULTS

3.1. External contextual grammars

When we speak about contextual grammars in this subsection, we mean contextual grammars with external derivation (also called external contextual grammars). A language of an external contextual grammar is a language which is externally generated.

In [3], contextual grammars were investigated where the selection languages are finite, monoidal, combinational, definite, nilpotent, commutative, or suffix-closed and a hierarchy of the language families generated was presented. In the papers [7, 26], results on the power of external contextual grammars with circular, ordered, union-free, or definite selection languages are given. The language families generated by such systems were inserted into the hierarchy from [3]. Furthermore, subregular language families F_n were considered and integrated which are obtained by restricting to n states, non-terminal symbols, or production rules to accept or to generate regular languages [28]. We consider here only subregular families defined by structural properties (not resources).

We now present a witness language to prove a proper inclusion and incomparabilities regarding ordered languages as selection languages.

Lemma 3.1. *Let $L_{ORD, \neg SLT} = \{a\}^* \cup \{a\}^* \{b\} \{a\}^* \cup \{c\} \{a\}^* \{b\} \{a\}^* \{c\}$. Then*

$$L_{ORD, \neg SLT} \in \mathcal{EC}(ORD) \setminus \mathcal{EC}(SLT).$$

Proof. The language $L_{ORD, \neg SLT}$ can be generated by the contextual grammar

$$(\{a, b, c\}, \{(\{a, b\}^*, \{(\lambda, a), (a, \lambda)\}), (\{a\}^* \{b\} \{a, b\}^*, \{(c, c)\})\}, \{\lambda, b\})$$

where the selection languages are ordered: For $\{a, b\}^*$, only one state is needed; the other selection language is accepted by a deterministic finite automaton where the transition function is given by $\delta(z_0, a) = z_0$ and $\delta(z_0, b) = z_1 = \delta(z_1, a) = \delta(z_1, b)$.

Assume that the language $L_{ORD, \neg SLT}$ can be generated by a contextual grammar with strictly locally testable selection languages. The subset

$$\{c\} \{a\}^* \{b\} \{a\}^* \{c\}$$

of $L_{ORD, \neg SLT}$ is infinite. Therefore, there is an infinite selection language

$$S \subseteq \{a\}^* \{b\} \{a\}^*$$

which is used to obtain words of the set $\{c\} \{a\}^* \{b\} \{a\}^* \{c\}$. Hence, to S belongs some context (u, v) with $u \in \{c\} \{a\}^*$ and $v \in \{a\}^* \{c\}$. If S is a strictly locally k -testable language, then $S = [B, I, E, F]$ and $a^k \in B \cap I \cap E$. Then, we have also $a^k \in S$. Therefore, a word from the set $\{c\} \{a\}^* \{c\}$ is generated which does not belong to the language $L_{ORD, \neg SLT}$. This contradiction implies that $L_{ORD, \neg SLT} \notin \mathcal{EC}(SLT)$. $\square$

We now prove the mentioned proper inclusion.

Lemma 3.2. *The proper inclusion $\mathcal{EC}(SLT_1) \subset \mathcal{EC}(ORD)$ holds.*

Proof. The inclusion $\mathcal{EC}(SLT_1) \subseteq \mathcal{EC}(ORD)$ follows from the Lemmas 2.8 and 2.11. A witness language for the properness is $L_{ORD, \neg SLT} \in \mathcal{EC}(ORD) \setminus \mathcal{EC}(SLT)$ from Lemma 3.1. $\square$

Many incomparability results have been published in [3, 4, 28]. The only open questions are whether the class $\mathcal{EC}(ORD)$ is incomparable to the classes $\mathcal{EC}(SLT)$ and $\mathcal{EC}(SLT_k)$ for $k \geq 2$. With the following results, we close this gap.

Lemma 3.3. *There is a language $L_{SLT_2, \neg ORD} \in \mathcal{EC}(SLT_2) \setminus \mathcal{EC}(ORD)$.*

Proof. Let

$$\begin{aligned} V &= \{a, b, c, d\}, \\ L &= \{d\}((\{a\}^+ \cup \{b\}^+ \cup \{c\}^+)\{d\})^+ \text{ and} \\ L_{SLT_2, \neg ORD} &= V^+ \cup \{e\}L\{e\}. \end{aligned}$$

We first show that $L_{SLT_2, \neg ORD} \in \mathcal{EC}(SLT_2)$. Let

$$G = (V \cup \{e\}, \{(V^+, \{(\lambda, x) \mid x \in V\}), (L, \{(e, e)\})\}, V).$$

From the axioms, we obtain by the first selection component all words of the sublanguage V^+ and by the second selection component all words of the sublanguage $\{e\}L\{e\}$. Hence, $L_{SLT_2, \neg ORD} = L(G)$.

The language V^+ is a strictly locally 1-testable language since it is represented by $[V, V, V, \emptyset]$. The other selection language L is a strictly locally 2-testable language since it is represented by $[B, I, E, \emptyset]$ with $B = \{da, db, dc\}$, $E = \{ad, bd, cd\}$, and $I = \{aa, bb, cc\} \cup B \cup E$. Hence, $L_{SLT_2, \neg ORD} \in \mathcal{EC}(SLT_2)$.

We now show that $L_{SLT_2, \neg ORD} \notin \mathcal{EC}(ORD)$. Suppose that there is a contextual grammar

$$G' = (V \cup \{e\}, \mathcal{P}, A_{G'})$$

with $L(G') = L_{SLT_2, \neg ORD}$ and the property that, in every selection component $(S, C) \in \mathcal{P}$, the selection language S is accepted by an ordered deterministic finite automaton. Since $L(G') = L_{SLT_2, \neg ORD}$ and the language L is infinite, the set $\mathcal{P}$ contains a selection component (S, C) where the context (e, e) is contained in the set C and S is a subset of L .

We now consider all and only those selection components where the context (e, e) is contained. Assume that for every such selection language S and every word $p \in V^*$ there are a natural number $n \geq 1$ and a letter $x \in \{a, b, c\}$ such that for every word $w \in S$ the word pdx^n is not a prefix of the word w . Then there are a selection language $S_{\neg x_1}$ (with $x_1 \in V$) and $n_1 \geq 1$ such that every word $w \in S_{\neg x_1}$ does not contain $dx_1^{n_1}$ as a prefix. Since every word of the language L occurs in some selection language, there is a selection language $S_{x_1, \neg x_2}$ (with $x_2 \in V$) which contains a word with the prefix $dx_1^{n_1}$. According to our assumption, there is a natural number $n_2 \geq 1$ such that every word $w \in S_{x_1, \neg x_2}$ does not contain $dx_1^{n_1}dx_2^{n_2}$ as a prefix. Further, there are a letter $x_3 \in V$, a selection language $S_{x_1, x_2, \neg x_3}$, and a natural number $n_3 \geq 1$ such that $dx_1^{n_1}dx_2^{n_2}$ occurs as a prefix in some word of $S_{x_1, x_2, \neg x_3}$ but not $dx_1^{n_1}dx_2^{n_2}dx_3^{n_3}$. From this argumentation follows that there are infinitely many selection languages which is a contradiction. Therefore, the assumption does not hold but the contrary: There are a selection language (for inserting the context (e, e)) and a word $p \in V^*$ such that for all $n \geq 1$ and all letters $x \in V$ there is a word $w \in S$ such that pdx^n is a prefix of the word w , more formally:

$$\exists S \exists p \in V^* \forall n \geq 1 \forall x \in V \exists v \in V^* : pdx^n v \in S.$$

Let S be such a selection language, p be such a word, and $A = (V, Z, z_0, F, \delta)$ a deterministic finite automaton which accepts the language S and is ordered. Additionally, for every word $w \in V^*$, let $[w] = \delta(z_0, w)$ be the state of the automaton A after reading the word w . The states $[pda]$, $[pdb]$, and $[pdc]$ are pairwise different as can be seen as follows: All the words pda^n , pdb^n , and pdc^n with $n \geq 1$ occur as prefixes of words in S . The state $[pda]$ differs from the states $[pdb]$ and $[pdc]$ because there is a word aw such that $[pdaaw] \in F$ but $[pdbaw] \notin F$ and $[pdcaw] \notin F$. The state $[pdb]$ differs additionally from the state $[pdc]$ because there is a word bw such that $[pdbbw] \in F$ but $[pdcbw] \notin F$. Let

$$[pda] \prec [pdb] \prec [pdc].$$

Due to the structure of the language L , the other possibilities (permutations of the letters a , b , and c) do not need to be considered. The state $[pd]$ differs from each of the states $[pda]$, $[pdb]$, and $[pdc]$ because there is a word cw such that $[pdcw] \in F$ but $[pdacw] \notin F$ and $[pdbcw] \notin F$ and there is a word aw such that $[pdaw] \in F$ but $[pdcaw] \notin F$. We now investigate all possibilities for the position of the state $[pd]$ in the order of states (this is similar to the case distinction in the proof of Lem. 2.7).

- (1) $[pd] \prec [pda]$: Then $[pdb] \preceq [pdab]$. Since $[pda] \prec [pdb]$, we also have $[pdab] \preceq [pdbb]$. Hence, $[pdb] \preceq [pdab] \preceq [pdbb]$. By iteration, we obtain

$$[pdb] \preceq [pdab] \preceq [pdbb] \preceq \cdots \preceq [pdab^i] \preceq [pdbb^i].$$

Since there are only finitely many states, there is a number $n \geq 1$ such that $[pdb^n] = [pdab^n] = [pdbb^n]$ but $[pdab^n] \notin F$ whereas $[pdbb^n] \in F$ which is a contradiction.

- (2) $[pda] \prec [pd] \prec [pdb]$: Then $[pdc] \preceq [pdbc]$. Since $[pdb] \prec [pdc]$, we also have $[pdbc] \preceq [pdcc]$. Hence, $[pdc] \preceq [pdbc] \preceq [pdcc]$. By iteration, we obtain

$$[pdc] \preceq [pdbc] \preceq [pdcc] \preceq \cdots \preceq [pdbc^i] \preceq [pdcc^i].$$

Since there are only finitely many states, there is a number $n \geq 1$ such that $[pdc^n] = [pdbc^n] = [pdcc^n]$ but $[pdbc^n] \notin F$ whereas $[pdcc^n] \in F$ which is a contradiction.

- (3) $[pdb] \prec [pd] \prec [pdc]$: Then $[pdba] \preceq [pda]$. Since $[pda] \prec [pdb]$, we also have $[pdaa] \preceq [pdba]$. Hence, $[pdaa] \preceq [pdba] \preceq [pda]$. By iteration, we obtain

$$[pdaa^i] \preceq [pdba^i] \preceq \cdots [pdaa] \preceq [pdba] \preceq [pda].$$

Since there are only finitely many states, there is a number $n \geq 1$ such that $[pdaa^n] = [pdba^n] = [pda^n]$ but $[pdba^n] \notin F$ whereas $[pda^n] \in F$ which is a contradiction.

- (4) $[pdc] \prec [pd]$: Then $[pdc] \preceq [pdb]$. Since $[pdb] \prec [pdc]$, we also have $[pdbb] \preceq [pdc]$. Hence, $[pdbb] \preceq [pdc] \preceq [pdb]$. By iteration, we obtain

$$[pdbb^i] \preceq [pdc] \preceq \cdots [pdbb] \preceq [pdc] \preceq [pdb].$$

Since there are only finitely many states, there is a number $n \geq 1$ such that $[pdbb^n] = [pdc] = [pdb^n]$ but $[pdc] \notin F$ whereas $[pdb^n] \in F$ which is a contradiction.

Thus, the selection language S is not accepted by an ordered deterministic finite automaton which is a contradiction to the assumption that every selection language of the contextual grammar G' is ordered. Therefore, $L_{SLT_2, \neg ORD} \notin \mathcal{EC}(ORD)$ and together with the first part, the statement of the lemma is proved. $\square$

Lemma 3.4. *The class $\mathcal{EC}(ORD)$ is incomparable to the classes $\mathcal{EC}(SLT)$ and $\mathcal{EC}(SLT_k)$ for $k \geq 2$.*

Proof. Due to the inclusion relations, it suffices to show that there are languages

$$L_1 \in \mathcal{EC}(SLT_2) \setminus \mathcal{EC}(ORD) \quad \text{and} \quad L_2 \in \mathcal{EC}(ORD) \setminus \mathcal{EC}(SLT).$$

From Lemma 3.3, we know for $L_1 = L_{SLT_2, \neg ORD}$ that

$$L_1 \in \mathcal{EC}(SLT_2) \setminus \mathcal{EC}(ORD).$$

From Lemma 3.1, we have

$$L_2 \in \mathcal{EC}(ORD) \setminus \mathcal{EC}(SLT)$$

3.2. Internal contextual grammars

When we speak about contextual grammars in this subsection, we mean contextual grammars with internal derivation (also called internal contextual grammars). A language of an internal contextual grammar is a language which is internally generated.

In [8], such contextual grammars were investigated where the selection languages belong to families F_n which are obtained by restriction to n states or n non-terminal symbols, productions, or symbols to accept or to generate regular languages and the effect of finite, monoidal, nilpotent, combinational, definite, ordered, regular commutative, regular circular, regular suffix-closed, and union-free selection languages on the generative capacity of internal contextual grammars was studied. We consider here only subregular families defined by structural properties (not resources).

In contrast to the external derivation mode, contextual grammars can internally apply a context infinitely often if it can be applied once. If a word contains a subword which belongs to a selection language, also the word after inserting the context contains a subword (namely the same as before) which belongs to this selection language. This difference has as a consequence that finite selection languages not only yield finitely many words as in the case of contextual grammars working in the external mode. Another consequence is that ‘outer’ parts of a word do not have to be added at the end of the derivation process but can be produced at some time whereas ‘inner’ parts can be ‘blown up’ later. For this reason, the results obtained for external contextual grammars are not of much help here.

According to Lemma 2.11, we have the inclusion $\mathcal{IC}(X) \subseteq \mathcal{IC}(Y)$ whenever we have the proper inclusion $X \subset Y$ for two families of languages X and Y .

We now present witness languages for proving the properness of the inclusions

$$\mathcal{IC}(\text{COMB}) \subset \mathcal{IC}(\text{SLT}_1) \subset \mathcal{IC}(\text{SLT}_2) \subset \dots \subset \mathcal{IC}(\text{SLT}_k) \subset \dots \subset \mathcal{IC}(\text{SLT})$$

and $\mathcal{IC}(\text{DEF}) \subset \mathcal{IC}(\text{SLT}) \subset \mathcal{IC}(\text{NC})$.

Lemma 3.7. *Let $L = \{ac^nbd^n \mid n \geq 0\}$. Then $L \in \mathcal{IC}(\text{SLT}_1) \setminus \mathcal{IC}(\text{COMB})$.*

Proof. The internal contextual grammar $(\{a, b, c, d\}, \{(\{b\}^+, \{(c, d)\})\}, \{ab\})$ with the strictly locally 1-testable selection language $\{b\}^+$ (which has a representation as $[\{b\}, \{b\}, \{b\}, \emptyset]$) generates the language L . Thus, $L \in \mathcal{IC}(\text{SLT}_1)$.

Assume that $L = L(G)$ for some internal contextual grammar G with combinational selection languages. Then, for sufficiently large n (which is larger than the sum of the longest length of axioms in G and the maximum of $|uv|$ for contexts (u, v) of G), we have a derivation $x \Rightarrow ac^nbd^n$. Because $x \in L$ holds, the used context (α, β) contains no letter a and no letter b (otherwise, we can produce a word with more than two occurrences of a or b), we have $x = ac^mbd^m$, $\alpha = c^{n-m}$, $\beta = d^{n-m}$, and the context is wrapped around a subword c^tbd^s for some numbers t and s with $m \geq t \geq 0$, $m \geq s \geq 0$. Since the selection language C is combinational, we get $ac^mbd^s \in C$ by $c^tbd^s \in C$. Therefore, we have the derivation $x = ac^mbd^sd^{m-s} \Rightarrow \alpha ac^mbd^s \beta d^{m-s} = c^{n-m}ac^mbd^m$, i. e., we can derive a word not in L . Thus, $L \notin \mathcal{IC}(\text{COMB})$. $\square$

Lemma 3.8. *Let n be a natural number with $n \geq 2$ and*

$$L_n = \{a^mb^{2n}c^m \mid m \geq n\} \cup \{a^{n-1}b^nc^{n-1}\}.$$

Then $L_n \in (\mathcal{IC}(\text{SLT}_n) \cap \mathcal{IC}(\text{FIN})) \setminus \mathcal{IC}(\text{SLT}_{n-1})$.

Proof. Let n be a natural number with $n \geq 2$ and L_n the language mentioned in the claim. The language L_n is generated by the contextual grammar

$$(\{a, b, c\}, \{([\{a^n\}, \{a, b, c\}^n, \{c^n\}, \emptyset], \{(a, c)\})\}, \{a^nb^{2n}c^n, a^{n-1}b^nc^{n-1}\})$$

with a selection language from the family SLT_n and by

$$(\{a, b, c\}, \{(\{b^{2n}\}, \{(a, c)\})\}, \{a^n b^{2n} c^n, a^{n-1} b^n c^{n-1}\})$$

with a finite selection language.

The language L_n is not generated by a contextual grammar where all selection languages belong to the family SLT_{n-1} . Assume the contrary. Since the subset $\{a^m b^{2n} c^m \mid m \geq n\}$ of L_n is infinite, there is a selection language $S = [B, I, E, F]$ used with a word $a^p b^{2n} c^q$ for two natural numbers $p \geq 0$ and $q \geq 0$. As $S \in SLT_{n-1}$, we have $b^{n-1} \in I$. Then also the word $a^p b^n c^q$ belongs to the selection language which is a subword of the word $a^{n-1} b^n c^{n-1} \in L_n$. Hence, another word with exactly n letters b would be generated which is a contradiction to the form of the words in the language L_n . $\square$

Lemma 3.9. *Let $L = \{a^n b^m c^n d^m \mid m \geq 1, n \geq 1\}$. Then*

$$L \in \mathcal{IC}(SLT_1) \setminus \mathcal{IC}(DEF).$$

Proof. The language L can be generated by the contextual grammar

$$G = (\{a, b, c, d\}, \{(S_{ac}, \{(a, c)\}), (S_{bd}, \{(b, d)\})\}, \{abcd\})$$

with the strictly locally 1-testable selection languages $S_{ac} = \{a\}\{b\}^*\{c\}$ and $S_{bd} = \{b\}\{c\}^*\{d\}$:

$$S_{ac} = [\{a\}, \{b\}, \{c\}, \emptyset] \quad \text{and} \quad S_{bd} = [\{b\}, \{c\}, \{d\}, \emptyset].$$

Assume that the language L can be generated by a contextual grammar G' with definite selection languages. Let $S_i = A_i \cup V^* B_i$ for $1 \leq i \leq q$ be the selection languages of G' . Further, let

$$p = \max \left\{ |w| \mid w \in \bigcup_{i=1}^q (A_i \cup B_i) \right\}.$$


Since the language L is infinite and the number of the letters a and b are unbounded in its words, there is a word $a^r b^s c^r d^s \in L$ with $r \geq p$ and $s \geq p$ such that from this word another one is generated. Hence, there is a selection language S_i with $1 \leq i \leq q$ which contains a word which is a subword of $a^r b^s c^r d^s$. This word is $a^{r'} b^{s'} c^{r''} d^{s''}$ with $1 \leq r' \leq r$ and $1 \leq r'' \leq r$ or $b^{s'} c^{r'} d^{s''}$ with $1 \leq s' \leq s$ and $1 \leq s'' \leq s$ in order to maintain the form of the words of the language. Since S_i is definite and $s - 1 + r'' \geq p$ or $r - 1 + s'' \geq p$, the word $b^{s-1} c^{r''}$ or $c^{r-1} d^{s''}$ also belongs to the selection language S_i . But then a letter a would be inserted inside the b -block or a letter b would be inserted inside the c -block. In both cases, a word would be generated which does not belong to the language L . Therefore, the language L cannot be generated by a contextual grammar with definite selection languages. $\square$

Lemma 3.10. *Let $L = \{a^{p_1} b a^{p_2} b a^{p_3} b a^{p_4+p_1} b a^{p_2} b a^{p_3} b a^{p_4} \mid p_i \geq 1, 1 \leq i \leq 4\}$. Then $L \in \mathcal{IC}(ORD) \setminus \mathcal{IC}(SLT)$.*

Proof. The language L can be generated by the contextual grammar

$$(\{a, b\}, \{(\{a\}^*\{b\}\{a\}^*\{b\}\{a\}^*\{b\}\{a\}^*, \{(a, a)\})\}, \{abababaabababa\})$$

where the selection language is ordered since it is accepted by the deterministic finite automaton shown below where the transition function is given by the table next to it (the order is $z_0 \preceq z_1 \preceq z_2 \preceq z_3 \preceq z_4$, the start state is z_0 , the accepting state is z_3):



Assume that the language L can be generated by a contextual grammar with strictly locally testable selection languages. The length of each a -block is unbounded. Therefore, there is an infinite selection language

$$S \subseteq \{a\}^* \{b\} \{a\}^* \{b\} \{a\}^* \{b\} \{a\}^*$$

used where the lengths of the a -blocks between the letters b are unbounded (otherwise, there would be a maximal length of one of the a -blocks in the words of the language L) and which has a context (a^l, a^l) associated to it (otherwise, a word would be generated which has not the required form of the words of the language L). If S is a strictly locally k -testable language, then it contains with a word $a^q b a^r b a^s b a^t$ with $q \geq 0$, $r \geq k$, $s \geq k$, and $t \geq 0$ also the word $a^q b a^r b a^s b a^t$. Adding the context (a^l, a^l) around such a subword of a word of L would yield a word which does not belong to the language L (a word with a wrong format). This contradiction implies that $L \notin \mathcal{IC}(SLT)$. $\square$

We now prove the proper inclusions mentioned above.

Theorem 3.11. *The relations*

$$\mathcal{IC}(COMB) \subset \mathcal{IC}(SLT_1) \subset \mathcal{IC}(SLT_2) \subset \cdots \subset \mathcal{IC}(SLT_k) \subset \cdots \subset \mathcal{IC}(SLT)$$

and $\mathcal{IC}(DEF) \subset \mathcal{IC}(SLT) \subset \mathcal{IC}(NC)$ hold.

Proof. The inclusions follow from the inclusions of the underlying language families (see [18, 21]) and Lemma 2.11. The properness is shown by the witness languages in the previous lemmas:

$$\begin{aligned} \mathcal{IC}(COMB) &\subset \mathcal{IC}(SLT_1) \text{ according to Lemma 3.7,} \\ \mathcal{IC}(SLT_1) &\subset \mathcal{IC}(SLT_2) \subset \cdots \subset \mathcal{IC}(SLT_k) \subset \cdots \subset \mathcal{IC}(SLT) \text{ due to Lemma 3.8,} \\ \mathcal{IC}(SLT) &\subset \mathcal{IC}(NC) \text{ according to Lemma 3.10, since } \mathcal{IC}(ORD) \subseteq \mathcal{IC}(NC) \text{ [28],} \\ \mathcal{IC}(DEF) &\subset \mathcal{IC}(SLT) \text{ due to Lemma 3.9, since } \mathcal{IC}(SLT_1) \subset \mathcal{IC}(SLT). \end{aligned}$$

$\square$

Lemma 3.12. *The proper inclusion $\mathcal{IC}(SLT_1) \subset \mathcal{IC}(ORD)$ holds.*

Proof. The inclusion $\mathcal{IC}(SLT_1) \subseteq \mathcal{IC}(ORD)$ follows from the Lemmas 2.8 and 2.11. A witness language for the properness is the language $L \in \mathcal{IC}(ORD) \setminus \mathcal{IC}(SLT)$ from Lemma 3.10. $\square$

The incomparabilities of the families $\mathcal{IC}(COMM)$ and $\mathcal{IC}(CIRC)$ with the families $\mathcal{IC}(SLT_k)$ for $k \geq 1$ and $\mathcal{IC}(SLT)$ follow from the incomparabilities of the sets $\mathcal{IC}(COMM)$ and $\mathcal{IC}(CIRC)$ with the sets $\mathcal{IC}(COMB)$ and $\mathcal{IC}(NC)$ shown in [28], since

$$\mathcal{IC}(COMB) \subseteq \mathcal{IC}(SLT_1) \subseteq \mathcal{IC}(SLT_2) \subseteq \cdots \subseteq \mathcal{IC}(SLT) \subseteq \mathcal{IC}(NC).$$

Regarding $\mathcal{IC}(SUF)$, we know from [8] that there is a language in the set $\mathcal{IC}(COMB) \setminus \mathcal{IC}(SUF)$ which also belongs to each set $\mathcal{IC}(SLT_k)$ for $k \geq 1$ and $\mathcal{IC}(SLT)$ due to the inclusion relations. However, it is still open whether there is a language in the set $\mathcal{IC}(SUF) \setminus \mathcal{IC}(NC)$ (which would not belong to subsets of $\mathcal{IC}(NC)$ either). So, we cannot use the method as for the classes $\mathcal{IC}(COMM)$ and $\mathcal{IC}(CIRC)$.

In the sequel, we show that, for every number $k \geq 1$, there is a language which belongs to the set $\mathcal{IC}(SUF)$ but not to $\mathcal{IC}(SLT_k)$. We first note that the internal contextual grammar

$$(\{c, d\}, \{(\{c, d\}^*, \{(c, d)\})\}, \{\lambda\})$$

generates the Dyck language D over $\{c, d\}$. For $k \geq 1$, we set

$$\begin{aligned} K'_k &= \{c^{m_0}ac^{m_1}a \dots c^{m_k}ac^{m_{k+1}}bd^{m_0+m_1+\dots+m_{k+1}} \mid m_i \geq 0, 0 \leq i \leq k+1\}, \\ K''_k &= K'_k \cup \{c^k a^{2k-1}\} K'_k \{d^k\}, \end{aligned}$$

and define K_k as the language obtained from K''_k by inserting a word of D at any position.

Lemma 3.13. *For all $k \geq 1$, we have $K_k \in \mathcal{IC}(SUF) \setminus \mathcal{IC}(SLT_k)$.*

Proof. The internal contextual grammar

$$(\{a, b, c, d\}, \{(\{a^r b \mid 0 \leq r \leq k+1\} \cup \{\lambda\}, \{(c, d)\})\}, \{a^{k+1}b, c^k a^{3k} b d^k\})$$

with a suffix closed selection language generates the language K_k . Thus, we have $K_k \in \mathcal{IC}(SUF)$.

Assume that $K_k = L(G)$ for some internal contextual grammar G where all selection languages are strictly locally k -testable. Let n be sufficiently large. Then there is a derivation $x \Rightarrow c^n a^{k+1} b d^n \in K_k$. Since $x \in K_k$ holds, the used context (α, β) contains no letter a and no letter b . We have $x = c^m a^{k+1} b d^m$, $\alpha = c^{n-m}$, $\beta = d^{n-m}$, and the context is wrapped around a subword $c^t a^{k+1} b d^s$ for some numbers t and s with $m \geq t \geq 0$ and $m \geq s \geq 0$.

Let $t \geq k$. Since the strictly locally k -testable selection language C which is used contains the word $c^t a^{k+1} b d^s$, it also contains the word $c^k a^{3k} b d^s$. Analogously, if $s \geq k$, the selection language C also contains the word $c^t a^{3k} b d^k$. Let $k' = \min\{k, t\}$ and $k'' = \min\{k, s\}$. Then we have $c^{k'} a^{3k} b d^{k''} \in C$. Hence, we have the derivation

$$c^k a^{3k} b d^k \Rightarrow c^{k-k'} \alpha c^{k'} a^{3k} b d^{k''} \beta d^{k-k''} = c^{k+n-m} a^{3k} b d^{k+n-m}$$

which produces a word not in K_k . Therefore, $K_k \notin \mathcal{IC}(SLT_k)$. $\square$

Together with the result $\mathcal{IC}(COMB) \setminus \mathcal{IC}(SUF) \neq \emptyset$ (recalled from [8]) which also implies that $\mathcal{IC}(SLT_k) \setminus \mathcal{IC}(SUF) \neq \emptyset$ for all $k \geq 1$, we obtain the following incomparability result.

Lemma 3.14. *The families $\mathcal{IC}(SLT_k)$ for $k \geq 1$ are incomparable to the family $\mathcal{IC}(SUF)$.*

It is left open, whether the family $\mathcal{IC}(SUF)$ is also incomparable to the family $\mathcal{IC}(SLT)$ or whether it is a proper subset (since we know already the relation $\mathcal{IC}(SLT) \setminus \mathcal{IC}(SUF) \neq \emptyset$).

Now we investigate the relations of the families $\mathcal{IC}(FIN)$, $\mathcal{IC}(NIL)$, and $\mathcal{IC}(DEF)$ to the families $\mathcal{IC}(SLT_k)$ for $k \geq 1$ as well as the relation of the family $\mathcal{IC}(SLT)$ to the family $\mathcal{IC}(ORD)$.

Lemma 3.15. *The families $\mathcal{IC}(SLT_k)$ for $k \geq 1$ are incomparable to the families $\mathcal{IC}(FIN)$, $\mathcal{IC}(NIL)$, and $\mathcal{IC}(DEF)$.*

Proof. Due to the inclusion relations, it suffices to show that there are languages

$$L_0 \in \mathcal{IC}(SLT_1) \setminus \mathcal{IC}(DEF) \quad \text{and} \quad L_n \in \mathcal{IC}(FIN) \setminus \mathcal{IC}(SLT_n) \text{ for } n \geq 1.$$

From Lemma 3.9, we know for $L_0 = \{a^n b^m c^n d^m \mid m \geq 1, n \geq 1\}$ that

$$L_0 \in \mathcal{IC}(SLT_1) \setminus \mathcal{IC}(DEF).$$




FIGURE 4. Hierarchy of language families by internal contextual grammars with selection languages defined by structural properties. An edge label refers to the paper where the respective inclusion is proved.

From Lemma 3.8, we know

$$L_n = \{ a^m b^{2n} c^m \mid m \geq n \} \cup \{ a^{n-1} b^n c^{n-1} \} \in \mathcal{IC}(FIN) \setminus \mathcal{IC}(SLT_{n-1})$$

for $n \geq 2$. □

From [18] and by Lemma 2.11, we know the inclusion $\mathcal{IC}(SLT) \subseteq \mathcal{IC}(NC)$; from [28], we have the relation $\mathcal{IC}(ORD) \subseteq \mathcal{IC}(NC)$. Here, we have shown with Lemma 3.10 that there is a language in the family $\mathcal{IC}(ORD)$ which does not belong to the family $\mathcal{IC}(SLT)$. The question whether the family $\mathcal{IC}(SLT)$ is a proper subset of the family $\mathcal{IC}(ORD)$ or whether these two families are incomparable is left open. Summarizing, we have the following result.

Theorem 3.16. *The inclusion relations presented in Figure 4 hold. An arrow from an entry X to an entry Y depicts the proper inclusion $X \subset Y$; the dashed arrow from $\mathcal{IC}(ORD)$ to $\mathcal{IC}(NC)$ indicates that it is not known so far whether the inclusion is proper or whether equality holds. If two families are not connected by a directed path, then they are incomparable with the exception of the family $\mathcal{IC}(SUF)$ and the families $\mathcal{IC}(ORD)$, $\mathcal{IC}(NC)$, and $\mathcal{IC}(SLT)$ where $\mathcal{IC}(ORD) \not\subseteq \mathcal{IC}(SUF)$, $\mathcal{IC}(NC) \not\subseteq \mathcal{IC}(SUF)$, and $\mathcal{IC}(SLT) \not\subseteq \mathcal{IC}(SUF)$ hold, and with*

exception of the family $\mathcal{IC}(\text{ORD})$ and the families $\mathcal{IC}(\text{SLT}_k)$ for $k \geq 2$ and $\mathcal{IC}(\text{SLT})$, where $\mathcal{IC}(\text{ORD}) \not\subseteq \mathcal{IC}(\text{SLT}_k)$ for $k \geq 2$ and $\mathcal{IC}(\text{ORD}) \not\subseteq \mathcal{IC}(\text{SLT})$ hold.

4. CONCLUSIONS

The inclusion relations obtained for the families of languages generated by external or internal contextual grammars are in most cases the same as for the families where the selection languages are taken from.

For further research, the open questions already mentioned should be considered: What is the relation between the families $\mathcal{IC}(\text{SLT})$ and $\mathcal{IC}(\text{ORD})$, especially, is there a language in the set $\mathcal{IC}(\text{SLT}_2) \setminus \mathcal{IC}(\text{ORD})$? Is the family $\mathcal{IC}(\text{SUF})$ incomparable to the family $\mathcal{IC}(\text{SLT})$ or is it a proper subset? Additionally, it remains to investigate the relations of the family $\mathcal{IC}(\text{SUF})$ to the families $\mathcal{IC}(\text{ORD})$ and $\mathcal{IC}(\text{NC})$.

In [28], two independent hierarchies have been obtained for each type of contextual grammars, one based on selection languages defined by structural properties (as considered in this present paper), the other based on resources (number of non-terminal symbols, production rules, or states). These hierarchies should be merged.

The families of languages which are locally (k) -testable (not necessarily in the strict sense) are the Boolean closure of the families in the strict sense. For contextual grammars where the selection languages are intersections or unions of strictly locally (k) -testable languages, nothing has to be done since the classes SLT_k for $k \geq 1$ and SLT are closed under intersection and, for union in a selection pair $(S_1 \cup S_2, C)$, one can take several selection pairs (S_1, C) , (S_2, C) instead. It remains to investigate the impact of locally (k) -testable selection languages which are the complement of a strictly locally (k) -testable language.

Additionally, other subfamilies of regular languages could be taken into consideration. Recently, external contextual grammars have been investigated where the selection languages are ideals or codes [5, 6]. This research could be extended to internal contextual grammars with ideals or codes as selection languages.

Acknowledgements. This paper is a revised and extended version of our paper presented at NCMA 2022 [9].

REFERENCES

- [1] J.A. Brzozowski, *Regular Expression Techniques for Sequential Circuits*. PhD thesis, Princeton University, Princeton, NJ, USA, 1962.
- [2] J.A. Brzozowski, G. Jirásková and C. Zou, Quotient complexity of closed languages. *Theory Comput. Syst.* **54** (2014) 277–292.
- [3] J. Dassow, Contextual grammars with subregular choice. *Fundam. Inform.* **64** (2005) 109–118.
- [4] J. Dassow, Contextual languages with strictly locally testable and star free selection languages. *Anal. Univ. București* **62** (2015) 25–36.
- [5] J. Dassow, Grammars with control by ideals and codes. *J. Automata Lang. Combinatorics* **23** (2018) 143–164.
- [6] J. Dassow, Remarks on external contextual grammars with selection. *Theor. Comput. Sci.* **862** (2021) 119–129.
- [7] J. Dassow, F. Manea and B. Truthe, On external contextual grammars with subregular selection languages. *Theor. Comput. Sci.* **449** (2012) 64–73.
- [8] J. Dassow, F. Manea and B. Truthe, On subregular selection languages in internal contextual grammars. *J. Automata Lang. Combinatorics* **17** (2012) 145–164.
- [9] J. Dassow and B. Truthe, On the generative capacity of contextual grammars with strictly locally testable selection languages, in *12th International Workshop on Non-Classical Models of Automata and Applications (NCMA 2022)*, Debrecen, Hungary, August 26–27, 2022. *Proceedings*, edited by H. Bordihn, G. Horváth and G. Vaszil. Vol. 367 of *EPTCS*. Open Publishing Association (2022) 65–80.
- [10] P. Garcia, E. Vidal and J. Oncina, Learning locally testable languages in the strict sense, in *Proc. Algorithmic Learning Theory 1990*, edited by S. Arikawa, S. Goto, S. Ohsuga and T. Yokomori. Springer/Ohmsha (1990) 325–338.
- [11] F. Gécseg and I. Peak, *Algebraic Theory of Automata*. Akadémiai Kiadó, Budapest (1972).
- [12] A. Gill and L.T. Kou, Multiple-entry finite automata. *J. Comput. Syst. Sci.* **9** (1974) 1–19.
- [13] I.M. Havel, The theory of regular events II. *Kybernetika* **5** (1969) 520–544.
- [14] M. Holzer and B. Truthe, On relations between some subregular language families, in *Seventh Workshop on Non-Classical Models of Automata and Applications (NCMA)*, Porto, Portugal, August 31–September 1, 2015, *Proceedings*, edited by R. Freund, M. Holzer, N. Moreira and R. Reis. Vol. 318 of *books@ocg.at*. Österreichische Computer Gesellschaft (2015) 109–124.
- [15] S. Istrail, Gramatici contextuale cu selectiva regulata. *Stud. Cerc. Mat.* **30** (1978) 287–294.
- [16] M. Kudlek, On languages of cyclic words, in *Proc. Aspects of Molecular Computing*, edited by N. Jonoska, G. Păun and G. Rozenberg. Vol. 2950 of *LNCS*. Springer-Verlag (2004) 278–288.
- [17] S. Marcus, Contextual grammars. *Rev. Roum. Math. Pures Appl.* **14** (1969) 1525–1534.

- [18] R. McNaughton and S. Papert, Counter-free Automata. MIT Press, Cambridge, USA (1971).
- [19] G. Păun, Marcus Contextual Grammars. Kluwer Publ. House, Doordrecht (1998).
- [20] M. Perles, M.M. Rabin and E. Shamir, The theory of definite automata. *IEEE Trans. Electron. Comput.* **12** (1963) 233–243.
- [21] S.C. Raghizzi and P. San Pietro, From regular to strictly locally testable languages, in *8th International Conference WORDS 2011*. Vol. 63 of *EPTCS*, edited by P. Ambrož, Š. Holub and Z. Masáková (2011) 103–111.
- [22] G. Rozenberg and A. Salomaa, editors. Handbook of Formal Languages. Springer-Verlag, Berlin (1997).
- [23] H.J. Shyr, Free Monoids and Languages. Hon Min Book Co., Taichung, Taiwan (1991).
- [24] H.J. Shyr and G. Thierrin, Ordered automata and associated languages. *Taiwan J. Math.* **5** (1974) 9–20.
- [25] H.J. Shyr and G. Thierrin, Power-separating regular languages. *Math. Syst. Theory* **8** (1974) 90–95.
- [26] B. Truthe, A Relation Between Definite and Ordered Finite Automata, in *Sixth Workshop on Non-Classical Models of Automata and Applications (NCMA), Kassel, Germany, July 28–29, 2014, Proceedings*, edited by S. Bensch, R. Freund and F. Otto. Vol. 304 of *books@ocg.at*. Österreichische Computer Gesellschaft (2014) 235–247.
- [27] B. Truthe, Hierarchy of subregular language families. Technical report, Justus-Liebig-Universität Giessen, Institut für Informatik, IFIG Research Report 1801 (2018).
- [28] B. Truthe, Generative capacity of contextual grammars with subregular selection languages. *Fundam. Inform.* **180** (2021) 1–28.
- [29] B. Wiedemann. Vergleich der Leistungsfähigkeit endlicher determinierter Automaten. *Diplomarbeit, Universität Rostock*, 1978.



Please help to maintain this journal in open access!

This journal is currently published in open access under the Subscribe to Open model (S2O). We are thankful to our subscribers and supporters for making it possible to publish this journal in open access in the current year, free of charge for authors and readers.

Check with your library that it subscribes to the journal, or consider making a personal donation to the S2O programme by contacting subscribers@edpsciences.org.

More information, including a list of supporters and financial transparency reports, is available at <https://edpsciences.org/en/subscribe-to-open-s2o>.